



Full High-Definition Projection Primed for Home Cinema Viewing

FEATURES

- Full high definition 1080p (1920x1080) resolution for the best quality, sharpness and clarity of video
- Bright 2300 ANSI lumens and 55,000:1 high contrast ratio for vibrant and dazzling images
- ISF mode for day and night calibration
- Large 1.5x zoom for ease of use and installation
- Host of connectivity options including HDMI v1.4b, VGA-in, S-video, component and composite
- 3D-ready via DLP® Link™ and BluRay 3D movie playback
- Vertical lens shift for ease of installation
- VividMotion processor technology eliminates display motion blur in fast moving objects creating a fluid video stream

An outstanding home cinema projector with embedded VividMotion

The H1189 BIANCO with a Full HD 1080p resolution delivers 2,300 ANSI lumens of brightness with a high contrast ratio of 55,000:1. The projector includes the VividMotion technology that allows the smoothening of the picture during a fast pan movement. This feature is specially appreciated during the display of action movies and sport events. To ensure accurate colour and realistic reproduction, this model is also equipped with a six-segment color wheel. Easy to set up and install, the Vivitek H1189 BIANCO projector features a vertical lens shift for greater installation flexibility.



H1189 BIANCO SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	2300 ANSI Lumens
	Native Resolution	1080p (1920 x 1080)
	Max. Supported Resolution	WUXGA (1920 x 1200) @60Hz
	Native Aspect Ratio	16:9
	Contrast Ratio	55,000:1
	Keystone Correction	Vertical +/- 40°
Optical	Throw Ratio	1.39 - 2.09:1
	Zoom Ratio	1.5x
	Lens Shift (Based on Full Image Height)	Offset von 116% - 130%
	Image Size (Diagonal)	25.9" - 324.9" (0.66 - 8.25 m)
	Projection Distance	1.2 - 10 m
	Projection Lens	F = 2.418 - 2.97, f = 20.7 - 31.05 mm
	Offset (Based on Full Image Height)	Manueller Lens shift
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), 2D->3D, Keypad lock
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub), HDMI v.1.4 (x2), Component (YPbPr RCA x 3), Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), 12v Trigger (3.5mm Mini-Jack), RS-232, 3D-Sync, USB A (Power Only), USB miniB (Service)
General	Dimensions (W x D x H)	285 x 261 x 121.8 mm
	Weight	3.15 kg
	Power	Supply: AC 100-240V, 50/60Hz. Consumption: 240W (Eco. Mode), 290W (Normal Mode), <0.5W (Standby)
	Lamp Life and Type	3,000 / 4,000 / 5,000 Hours (Normal / Eco. / Dynamic Eco. Mode), 260W / 205W
	Speakers	10W
	Noise Level	34dB / 29db (Normal / Eco. Mode)
	Standard Accessories	VGA Cable, HDMI Cable, User Manual (CD), Lens Cap, Carrying Case, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (5811120259-SVV), 3D Glasses P/N (3534257700), Remote Control P/N (5041846400)
	Warranty	Standard Warranty: 3 years projector / 1 year on lamp or 1.000 hours whichever comes first
	UPC Code	813097023612